



	PART #	VIN.	NUT DIA.	STRENGTH	C	AF	AP	WGT.	COLOR	NOTE
USE WITH ROD BRACING	H0310	A	5/8 NUT	A563 Gr. C	0.625	1.063	1.250	0.116	BK,GZ	
	H0320	A	3/4" NUT	A563 Gr. C	0.750	1.250	1.438	0.182	BK,GZ	
	H0325	A	7/8" NUT	A563 Gr. C	0.875	1.438	1.625	0.297	BK,GZ	
	H0330	A	1" NUT	A563 Gr. C	1.000	1.625	1.875	0.406	BK,GZ	
	H0450	A	1 1/8" NUT	A563 Gr. A	1.125	1.688	1.938	0.403	BK,GZ	
	H0340	A	1 1/4" NUT	A563 Gr. DH	1.250	2.000	2.313	0.740	BK,GZ	

USE WITH A307 / A307 BUTTON HEAD										
	H0400	A	1/2" NUT	A563 Gr. A	0.500	0.750	0.875	0.034	BK,GZ	

USE WITH A325 BOLTS	H0300	A	1/2" NUT	A563 Gr. C	0.500	0.875	1.000	0.060	BK,GZ, ZI	2
	H0310	A	5/8 NUT	A563 Gr. C	0.625	1.063	1.250	0.116	BK,GZ	2
	H0320	A	3/4" NUT	A563 Gr. C	0.750	1.250	1.438	0.182	BK,GZ	2
	H0325	A	7/8" NUT	A563 Gr. C	0.875	1.438	1.625	0.297	BK,GZ	2
	H0330	A	1" NUT	A563 Gr. C	1.000	1.625	1.875	0.406	BK,GZ	2
	H0340	A	1 1/4" NUT	A563 Gr. DH	1.250	2.000	2.313	0.740	BK,GZ	
	H0350	A	1 1/2" NUT	A563 Gr. DH	1.500	2.375	2.750	1.310	BK,GZ	1

* GALVANIZED NUTS **MAY NOT** BE AVAILABLE AT YOUR DIVISION AND MAY REQUIRE A PURCHASE REQUEST, DEPENDING ON STOCKED AVAILABILITY.

NOTES

1. This nut is not stocked at all divisions, check with Purchasing for availability. A Purchase Request is required ASAP.
2. When using GZ or ZI Nuts with Hot-Dipped Galvanized or Electroplated Zinc A325 Bolts, these nuts are required to be Grade DH. These can be ordered with the H03__ mark numbers to be substituted by the vendor.